



# DIESEL API CF-4/CF/SG



## PERFORMANCES LEVELS

**API** CF-4/CF/SG

**SAE** 10W-40, 15W-40, 20W-50

## DESCRIPTION

AKross Diesel API CF-4/CF/SG is a series of high-quality multigrade motor oils produced on a synthetic and mineral based oil with the use of multifunctional additives.

## APPLICATIONS

AKross Diesel API CF-4/CF/SG oils are recommended to apply in modern high-speed, four-stroke, atmospheric and turbocharged diesel engines of trucks, vans, buses, minibuses and passenger cars. Also, it can be applied for naturally aspirated gasoline engines of cars and buses, for which the oils CF-4, CF, CD are recommended and for gasoline engines, which meet the environmental class 2.

## PROPERTIES AND SPECIFICATIONS

Properties	Method	AKROSS DIESEL		
		10W-40	15W-40	20W-50
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	ASTM D445	14,0	14,5	17,0
Density at 20°C, kg/m <sup>3</sup>	ASTM D 1298	870	880	890
Viscosity Index	ASTM D97	150	140	115
Flash Point, °C	ASTM D92	205	210	210
Pour Point, °C	ASTM D97	-35	-30	-25
Perchloric acid, mg KOH/g	ASTM D4739	8,0	8,0	8,0
Sulphated ash, wt %	ASTM D874	1,4	1,4	1,4

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.